

Note:
The A&Z(H) in the name means: A(H) and Z(H).


| ITEM | NAME OF PART | MATERIAL | NOTES |
|------|--------------|--------------|-----------|
| 6 | Screw | Steel | Zn Plated |
| 5 | Pin | Copper | Sn Plated |
| 4 | Cage | Copper Alloy | NI Plated |
| 3 | Din | PA66 | UL94V-0 |
| 2 | Cover | PA66 | UL94V-0 |
| 1 | Housing | PA66 | UL94V-0 |

| UL Standard: | B | C | D |
|--|-----------------|--------|--------|
| 额定电压/Rated Voltage(V)/Current(A) | 300/15 | / | 300/10 |
| IEC 标准/IEC Standard: | | | |
| 过压类别/Overvoltage Category/污染等级/Pollution Degree | III/3 | III/2 | II/2 |
| 额定电压/电流/Rated Voltage(V)/Current(A) | 250/12 | 320/12 | 630/12 |
| 额定脉冲电压/Rate Impulse Voltage (kV) | 4 | 4 | 4 |
| 螺丝 扭矩/Torque Tightening(N·m/Lb·in) | M3: 0.6/5/32 | | |
| 线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm ²) | 28~12 / 0.2~2.5 | | |
| 间距/Pitch(mm)/线数范围/Poles | 5.08/N=02~24P | | |
| 剥线长度/Stripping length(mm) | 7~8 | | |
| 使用温度范围/Operating temperature(°C) | -40~+105 | | |
| 符合RoHS环保要求/Conform to RoHS | Yes | | |
| 标准颜色编号/Standard color number: PANTONE/RAL | / | | |

MATERIAL: SURFACE: /

MAT NO.:
STATUS:
APPD:
CHKD:
DRT:

NAME:
DRAWING NO.:
ZESADK-5.08-XXP-1Y-00A&Z(H)



| 公差/General | tolerances(mm) |
|------------|----------------|
| 0 | >3 |
| 3 | >6 |
| 6 | >10 |
| 10 | >18 |
| 18 | >30 |
| 30 | >50 |
| 50 | >80 |
| 80 | >120 |
| 120 | >180 |
| 180 | >250 |
| 250 | >315 |
| 315 | >400 |
| 400 | >500 |
| 500 | >500 |
| 500 | >500 |
| ±2.50 | ±2.50 |

0.1/10
±Z

| SIZE: A4 | mm | inch | TYPE: | SCALE: | SHEET |
|----------|----|------|--------------|--------|-------|
| | | | DRAWING NO.: | | REV |
| | | | | | 1/1 |